




strands[®]


-lighting division




Part No. 809233
UNITY WORK LIGHT 11W LED




Part No. 809234, 809235
UNITY WORK LIGHT 10W LED




Part No. 809236
UNITY WORK LIGHT 19W LED




Part No. 809237
UNITY WORK LIGHT 31W LED



Part No. 809238
UNITY WORK LIGHT 64W LED



Part No. 809240
UNITY WORK LIGHT 92W LED



Part No. 809239
UNITY WORK LIGHT 149W LED

UNITY WORK LIGHT LED



PART NO.	809233	809234	809235	809236	809237	809238	809240	809239
VOLTAGE	9-40V DC	10-32V DC	10-32V DC	10-32V DC	10-40V DC	10-40V DC	10-40V DC	10-40V DC
CONSUMPTION	11W	10W	10W	19W	31W	64W	92W	149W
THEORETICAL LUMEN	1520	1520	1520	3040	2750	6187	15000	21600
ACTUAL LUMEN	1000	931	931	1942	2200	5200	7366	13000
IP-CLASS	IP68/IP69K	IP68	IP68	IP68	IP67/IP69K	IP67/IP69K	IP67/IP69K	IP67/IP69K
CONNECTION	DT-2	DT	DT	DT	DT	DT	DT	DT
CABLE LENGTH	500mm	500mm	500mm	250mm	520mm	520mm	500mm	200mm
MATERIAL HOUSING	Aluminum	Aluminum	Aluminum	Aluminum	Aluminum	Aluminum	Aluminum	Aluminum
MATERIAL LENS	Polycarbonate	Polycarbonate	Polycarbonate	Polycarbonate	Polycarbonate	Polycarbonate	Polycarbonate	Polycarbonate
LENGTH	-	52,11mm	52,11mm	-	70,4mm	101mm	110,27mm	135mm
DIAMETER	65mm	-	-	84,4mm	-	-	-	-
DEPTH	34mm	26,13mm	26,13mm	54,72mm	41mm	45mm	57,6mm	90,4mm
HEIGHT	65mm	67,03mm	67,03mm	-	85,2mm	114,4mm	110,26mm	118mm
HEIGHT INCLUDING BRACKET	86mm	112,2mm	112,2mm	112,2mm	95,5mm	120mm	144,13mm	152,2mm
OPERATING TEMPERATURE	-30°C · +65°C	-30°C · +65°C	-30°C · +65°C	-30°C · +80°C	-30°C · +65°C	-30°C · +65°C	-30°C · 65°C	-30°C · +65°C
E-APPROVED	No	ECE R23	No	No	No	No	No	No
EMC-CERTIFICATES	ECE R10	ECE R10	ECE R10	ECE R10, CISPR Class 2	ECE R10	ECE R10	ECE R10	ECE R10