strands®
-lighting division

Part No. 900001
RUBBERARM SMALL LEFT *LED*

Part No. 900002
RUBBERARM SMALL RIGHT *LED*

Part No. 900003
RUBBERARM MEDIUM LEFT *LED*

Part No. 900004
RUBBERARM MEDIUM RIGHT *LED*

Part No. 900005
RUBBERARM LARGE LEFT *LED*

Part No. 900006
RUBBERARM LARGE RIGHT *LED*

Part No. 900007
RUBBERARM XL LEFT *LED*

Part No. 900008
RUBBERARM XL RIGHT *LED*

FREEDOM LIGHT GUIDE POSITION LIGHTS *LED*

LED | 12-24V | 3,3W | IP6K9K | E

PART NO.	900001	900002	900003	900004	900005	900006	900007	900008
VOLTAGE	12-24V DC	12-24V DC	12-24V DC	12-24V DC	12-24V DC	12-24V DC	12-24V DC	12-24V DC
CONSUMPTION	3,3W	3,3W	3,3W	3,3W	3,3W	3,3W	3,3W	3,3W
FUNCTION	Front position, Rear position, Side position	Front position, Rear position, Side position	Front position, Rear position, Side position	Front position, Rear position, Side position	Front position, Rear position, Side position	Front position, Rear position, Side position	Front position, Rear position, Side position	Front position, Rear position, Side position
IP-CLASS	IP6K9K	IP6K9K	IP6K9K	IP6K9K	IP6K9K	IP6K9K	IP6K9K	IP6K9K
CONNECTION	Cable	Cable	Cable	Cable	Cable	Cable	Cable	Cable
CABLE LENGTH	1000 mm	1000 mm	1000 mm	1000 mm	1000 mm	1000 mm	1000 mm	1000 mm
MATERIAL HOUSING	Rubber	Rubber	Rubber	Rubber	Rubber	Rubber	Rubber	Rubber
MATERIAL LENS	Polycarbonate	Polycarbonate	Polycarbonate	Polycarbonate	Polycarbonate	Polycarbonate	Polycarbonate	Polycarbonate
COLOR LED	White, Red, Amber	White, Red, Amber	White, Red, Amber	White, Red, Amber	White, Red, Amber	White, Red, Amber	White, Red, Amber	White, Red, Amber
COLOR LENS	Dark clear	Dark clear	Dark clear	Dark clear	Dark clear	Dark clear	Dark clear	Dark clear
LENGTH	89 mm	89 mm	136 mm	136 mm	190 mm	190 mm	259 mm	259 mm
DEPTH	46 mm	46 mm	46 mm	46 mm	46 mm	46 mm	46 mm	46 mm
HEIGHT	104 mm	104 mm	116,9 mm	116,9 mm	160,5 mm	160,5 mm	207,5 mm	207,5 mm
CC	80 mm	80 mm	80 mm	80 mm	80 mm	80 mm	80 mm	80 mm
OPERATING TEMPERATURE	-40°C - +40°C	-40°C - +40°C	-40°C - +40°C	-40°C - +40°C	-40°C - +40°C	-40°C - +40°C	-40°C - +40°C	-40°C - +40°C
ADR APPROVED	No	No	No	No	No	No	No	No
E-APPROVED	ECE R148	ECE R148	ECE R148	ECE R148	ECE R148	ECE R148	ECE R148	ECE R148
EMC-CERTIFICATES	ECE R10	ECE R10	ECE R10	ECE R10	ECE R10	ECE R10	ECE R10	ECE R10