

strands®

-lighting division



Part No. 900031
GROUND-LINE POSITION LIGHT RED



Part No. 900032
GROUND-LINE POSITION LIGHT WHITE



Part No. 900033
GROUND-LINE POSITION LIGHT AMBER



Part No. 900034
GROUND-LINE POSITION LIGHT AMBER WITH INDICATOR

FREEDOM GROUND-LINE POSITION LIGHT



PART NO.	900031	900032	900033	900034
VOLTAGE	12-24V DC	12-24V DC	12-24V DC	12-24V DC
CONSUMPTION	2,2W	2,2W	2,2W	2,2W
FUNCTION	Rear position light	Front position light	side position light	Side position and side direction indicator
IP-CLASS	IP6K9K	IP6K9K	IP6K9K	IP6K9K
CONNECTION	Cable	Cable	Cable	Cable
CABLE LENGTH	500 mm	500 mm	500 mm	500 mm
MATERIAL HOUSING	PP	PP	PP	PP
MATERIAL LENS	PMMA	PMMA	PMMA	PMMA
COLOR LENS	Red	White tinted	Amber tinted	Amber tinted
COLOR LED	Warm white	Cool white	Warm white	Warm white
LENGTH	133,8 mm	133,8 mm	133,8 mm	133,8 mm
HEIGHT	53 mm	53 mm	53 mm	53 mm
DEPTH	47 mm	47 mm	47 mm	47 mm
HEIGHT INCLUDING BRACKET	70,7 mm	70,7 mm	70,7 mm	70,7 mm
CC	75 mm	75 mm	75 mm	75 mm
CC FOR BRACKET	30 mm or 50 mm	30 mm or 50 mm	30 mm or 50 mm	30 mm or 50 mm
OPERATING TEMPERATURE	-40°C.+40°C	-40°C.+40°C	-40°C.+40°C	-40°C.+40°C
ADR-APPROVED	No	No	No	No
E-APPROVED	ECE R148, ECE R150	ECE R148, ECE R150	ECE R148, ECE R150	ECE R148, ECE R150
EMC-CERTIFICATE	ECE R10	ECE R10	ECE R10	ECE R10